


Rodamiento conico

NP609202-NP357825-TIMKEN - NP609202-NP357825-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/np609202-np357825-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDI

TYPE TDI



| Bearing Dimensions | | | | Load Ratings | | | | | | | | | |
|--------------------|---------|---------|---------------------------|--|--------------------------------------|--------------------------------------|--------------------------------------|--|--|--|-------------------------|------|--|
| Bore d | O.D. D | Width T | Double Inner Ring Width B | Dynamic ⁽¹⁾ C ₁₀ | Static ⁽²⁾ C ₀ | Factor ⁽³⁾ Y ₁ | Factor ⁽³⁾ Y ₂ | Dynamic ⁽⁴⁾ C ₉₀ | Dynamic ⁽⁴⁾ C ₅₀ | Dynamic ⁽⁴⁾ C ₁₀ | Factor ⁽⁵⁾ K | | |
| mm | in. | mm | mm | N | kN | | | N | N | N | | | |
| 464.000 | 18.2677 | 615.000 | 150.000 | 136.000 | 321000 | 0.8 | 0.8 | 1.3 | 40400 | 59100 | 70300 | 0.73 | |
| | | 24.125 | 5.9055 | 5.3043 | 63200 | | | | 8060 | 12400 | 13800 | | |

| Part Number | | Dimensions | | | | Geometry Factors | | | Bearing Weight |
|-------------|----------|--|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max Shaft Fillet Radius r _s | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r _h | Backing Shoulder Dia. D _s | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | | | | lbm |
| NP609202 | NP357825 | 2.0 | 488.0 | 4.0 | 673.0 | 4002.4 | 478.0 | 0.2800 | 176.36 |
| | | 0.08 | 19.20 | 0.16 | 22.98 | | | | 206.54 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952371887 |
| Diámetro interior | 464 mm |
| Diámetro exterior | 615 mm |
| Espesor | 150 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE