

Rodamiento de agujas NA4956-IKO - NA4956-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/na4956-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Inner Ring

| Shaft dia. mm | Identification number | | | | | | Mass (Ref.) | | | |
|------------------------|-----------------------|---------------------------------|-----------------------------------|---------------------------------|---------------------------|--------------------------|---|----------------------|-----|---------------|
| | NA 49 | NA 69 | NA 48 | TAFI | TRI | GTRI | g | d | | |
| 280 | NA 4956 | — | — | — | — | — | 33 100 | 280 | | |
| Boundary dimensions mm | | Standard mounting dimensions mm | | | Basic dynamic load rating | Basic static load rating | Allowable rotational speed ⁽²⁾ | Assembled inner ring | | |
| D | C | B | r _s min ⁽¹⁾ | F _w S ⁽²⁾ | Min. d _s | Max. d _s | N | N | rpm | |
| 380 | 100 | — | 2.1 | 310 4 | 291 | 307 369 | 877 000 | 2 040 000 | 950 | LRT 280310100 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952373096 |
| Diámetro interior | 280 mm |
| Diámetro exterior | 380 mm |
| Espesor | 100 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE