


## Rodamiento de agujas NA4840-IKO - NA4840-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/na4840-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Inner Ring



Shaft dia. mm	Identification number						Mass (Ref.)						
	NA 49	NA 69	NA 48	TAFI	TRI	GTRI	g	d					
200	—	—	<b>NA 4840</b>	—	—	—	6 040	200					
Boundary dimensions mm		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring					
D	C	B	r <sub>s min</sub> <sup>(1)</sup>	F <sub>w</sub> <sup>(2)</sup>	S	Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.	N	N	rpm	LRT	20022050
250	50	—	1.5	220	1.5	208	218	242	255 000	766 000	1 600	LRT	20022050

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952373171
Diámetro interior	200 mm
Diámetro exterior	250 mm
Espesor	50 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE