


Rodamiento conico

H244848TD-H244810-TIMKEN - H244848TD-H244810-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/h244848td-h244810-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDIT

TYPE TDIT



Bearing Dimensions				Load Ratings												
Bore d	Taper	O.D. D	Width T	Double Inner Ring Width B	Dynami ⁽¹⁾ C ₁₀	Factor ⁽²⁾ Y ₁	Factor ⁽²⁾ Y ₂	Dynami ⁽³⁾ C ₉₀	Dynami ⁽³⁾ C ₅₀	Dynami ⁽³⁾ C ₁₀₀	Factor ⁽²⁾ K	Geometry Factors			Bearing Weight	
mm	°	mm	mm	mm	N			N	N	N		G ₁	G ₂	C ₃	kg	
219.075	1:12	358.775	196.850	206.820	202000	0.33	2.02	3.02	37600	21300	62000	1.76	1601.9	150.0	0.1040	83.34
8.6250		14.1250	7.7500	7.5750	56000				84200	47900	147000					163.74

Part Number		Shaft			Housing			Geometry Factors			Bearing Weight
Inner	Outer	Max Shaft Fillet Radius	Max Shaft Fillet Radius	Max Housing Fillet Radius	Max Housing Fillet Radius	Shoulder Dia. D _s	G ₁	G ₂	C ₃	kg	
H244848TD	H244810	1.5	6.4	0.25	0.25	202.8	1601.9	150.0	0.1040	83.34	
		0.50	0.25			12.72				163.74	

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952373324
Diámetro interior	219.075 mm
Diámetro exterior	358.775 mm
Espesor	196.85 mm
Peso	83340 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE