


## Rodamiento de agujas GBRI102216-IKO - GBRI102216-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri102216-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>15.875</b> (5/8)	<b>GBRI 102216</b>	133	15.875 <sub>0</sub> <sup>+</sup> <sub>0</sub>	34.925 <sub>0</sub> <sup>+</sup> <sub>0</sub>	25.400 <sub>0</sub> <sup>+</sup> <sub>0</sub>	25.650	22.225 <sub>0</sub> <sup>+</sup> <sub>0</sub>

Standard mounting dimensions mm		Basic dynamic load C <sub>10</sub> (N)	Limiting static load C <sub>0</sub> (N)	Allowable rotational speed <sup>(1)</sup> (rpm)	Assembled inner ring LRBZ 101416		
d <sub>a</sub> Min.	D <sub>a</sub> Max.						
21	21.2	30	0.6	38 300	58 300	7 000	

Notes:  
(1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377407
Diámetro interior	15.875 mm
Diámetro interior	5/8" inch
Diámetro exterior	34.925 mm
Diámetro exterior	1 3/8" inch
Espesor	25.65 mm
Espesor	1.01" inch
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE