


Rodamiento de agujas GBRI122416-IKO - GBRI122416-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri122416-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|--------------------------|---------------------|------------------------------|--------|--------|--------|----------------|
| | | | d | D | C | B | F _w |
| 19.050 (3/4) | GBRI 122416 | 150 | 19.050 | 38.100 | 25.400 | 25.650 | 25.400 |

| Standard mounting dimensions mm | | Ball diam. mm C | Basic dynamic load rating C ₀ N | Allowable rotational speed (P) rpm | Assembled inner ring LRBZ 121616 | | |
|------------------------------------|------------------------|-----------------------|---|---|-------------------------------------|-------|-------------|
| d _a Min. | d _a Max. | | | | | | |
| 24 | 24.4 | 33.3 | 0.6 | 41 400 | 67 100 | 6 000 | LRBZ 121616 |

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3663952377421 |
| Diámetro interior | 19.05 mm |
| Diámetro exterior | 38.1 mm |
| Espesor | 25.65 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE