


Rodamiento de agujas GBRI203316-IKO - GBRI203316-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri203316-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
31.750 (1 1/4)	GBRI 203316	235	31.750 (1)	52.388 (2)	25.400 (1)	25.650	38.100 (1 1/2)

Standard mounting dimensions mm		Ball diam. mm (inch)	Basic dynamic load rating C_0 N	Allowable rotational speed (2) rpm	Assembled inner ring LRBZ 202416		
d_a Min.	D_a Max.						
37	37.1	47.3	0.6	54 200	97 700	4 000	LRBZ 202416

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377469
Diámetro interior	31.75 mm
Diámetro exterior	52.388 mm
Espesor	25.65 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE