


Rodamiento de agujas GBRI243920-IKO - GBRI243920-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri243920-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
38.100 (1 1/2)	GBRI 243920	410	38.100 (1 1/2)	61.912 (2 3/8)	31.750 (1 1/4)	32.000	47.625 (1 7/8)

Standard mounting dimensions mm		Ball diam. mm (inch)	Basic dynamic load rating C ₀ N	Allowable rotational speed (P) rpm	Assembled inner ring		
d ₄ Min.	d ₄ Max.						
43.3	45	56.2	1	72 400	150 000	3 000	LRBZ 243020

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377520
Diámetro interior	38.1 mm
Diámetro exterior	61.912 mm
Espesor	32 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE