


## Rodamiento de agujas GBRI264116-IKO - GBRI264116-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri264116-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>41.275</b> (1 5/8)	<b>GBRI 264116</b>	350	41.275 (1 5/8)	65.088 (2 5/8)	25.400 (1)	25.650	50.800 (2)

Standard mounting dimensions mm				Basic dynamic load rating C <sub>0</sub> N	Limiting load rating C <sub>0</sub> N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 263216
d <sub>a</sub> Min.	d <sub>a</sub> Max.	D <sub>a</sub> Max.	r <sub>as max</sub> (2)				
48	49	59.2	1	63 100	130 000	3 000	LRBZ 263216

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377537
Diámetro interior	41.275 mm
Diámetro exterior	65.088 mm
Espesor	25.65 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE