


Rodamiento de agujas GBR405224-IKO - GBR405224-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr405224-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (°)	
			F	D	C	D _s Max.	r _{as} max
63.500 (2½)	GBR 405224	535	63.500 (3)½	82.550 (3)¼	38.100 (1)½	75.7	1.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(°)					
N	N	rpm					
120 000	248 000	2 500					

Notes: ⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377575
Diámetro interior	63.5 mm
Diámetro interior	2 1/2" inch
Diámetro exterior	82.55 mm
Diámetro exterior	3 1/4" inch
Espesor	38.1 mm
Espesor	1 1/2" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE