


Rodamiento de agujas GBR142212-IKO - GBR142212-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr142212-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _d	D	C	D _s Max.	r _{as} max
22.225 (⁽²⁾ ₀)	GBR 142212	71	22.225 ₀ ⁽²⁾	34.925 ₀ ⁽²⁾	19.050 ₀ ⁽²⁾	30	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾					
N	N	rpm					
28 600	40 100	7 000					

Notes:
(¹) Maximum permissible corner radius of the housing.
(²) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377711
Diámetro interior	22.225 mm
Diámetro exterior	34.925 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE