


Rodamiento de agujas GBR162412-IKO - GBR162412-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr162412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _e	D	C	D _s Max.	r _{as} max
25.400 (1)	GBR 162412	79	25.400 ₀	38.100 _{0.012}	19.050 _{0.002}	33.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
31 000	46 100	6 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377735
Diámetro interior	25.4 mm
Diámetro exterior	38.1 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE