


Rodamiento de agujas GBR162416-IKO - GBR162416-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr162416-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D _s Max.	r _{as max}
25.400 (1)	GBR 162416	106	25.400 (1)	38.100 (1 1/2)	25.400 (1)	33.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
41 400	67 100	6 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. No grease is preapplied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377742
Diámetro interior	25.4 mm
Diámetro exterior	38.1 mm
Espesor	25.4 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE