


Rodamiento de agujas GBR324116-IKO - GBR324116-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr324116-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm (⁽¹⁾) Max. | |
|-----------------------------------|---|---|---------------------------------|----------------|------------|--|---------------------|
| | | | F | D | C | D _s | r _{as max} |
| 50.800 (2) | GBR 324116 | 215 | 50.800 (2) | 65.088 (2 1/2) | 25.400 (1) | 59.2 | 1 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽³⁾ | | | | | |
| N | N | rpm | | | | | |
| 63 100 | 130 000 | 3 000 | | | | | |

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952377858 |
| Diámetro interior | 50.8 mm |
| Diámetro exterior | 65.088 mm |
| Espesor | 25.4 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE