


Rodamiento de agujas GBRI365628-IKO - GBRI365628-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri365628-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
57.150 (2 1/4)	GBRI 365628	1 130	57.150 (1) 0	88.900 (1) 0	44.450 (1) 0	44.700	69.850 (1) 0

Standard mounting dimensions mm				Basic dynamic load rating C ₀ N	Static load rating C ₁₀ N	Allowable rotational speed (1) rpm	Assembled inner ring
d _a Min.	d _a Max.	D _a Max.	r _{as max} (2)				
65	67	82	1.5	147 000	336 000	2 000	LRBZ 364428

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377926
Diámetro interior	57.15 mm
Diámetro exterior	88.9 mm
Espesor	44.45 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE