


Rodamiento de agujas GBRI406028-IKO - GBRI406028-IKO

https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri406028-iko

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
63.500 (2 1/2)	GBRI 406028	1 230	63.500 \pm 0.010	95.250 \pm 0.010	44.450 \pm 0.010	44.700	76.200 \pm 0.010

Standard mounting dimensions mm				Ball diam. mm C	Basic load rating N	Limiting load rating N	Allowable rotational speed (1) rpm	Assembled inner ring
d _a Min.	d _a Max.	D _a Max.	r _{as max} (1)					
71	73	88	1.5	154 000	368 000	2 000	LRBZ 404828	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952377940
Diámetro interior	63.5 mm
Diámetro exterior	95.25 mm
Espesor	44.45 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE