


Rodamiento de agujas GBRI446832-IKO - GBRI446832-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri446832-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|--------------------------|---------------------|------------------------------|-----------------|------------|--------|----------------|
| | | | d | D | C | B | F _w |
| 69.850 (2 3/4) | GBRI 446832 | 1 840 | 69.850 (2 3/4) | 107.950 (4 1/4) | 50.800 (2) | 51.050 | 82.550 (3 1/4) |

| Standard mounting dimensions mm | | | | Basic dynamic load rating C ₀ N | Static load rating C ₁₀ N | Allowable rotational speed (1) rpm | Assembled inner ring |
|------------------------------------|------------------------|------------------------|-------------------------|---|---|---|----------------------|
| d _a Min. | d _a Max. | D _a Max. | r _{as max} (2) | | | | |
| 77 | 79 | 99.9 | 1.5 | 214 000 | 452 000 | 1 800 | LRBZ 445232 |

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3663952377964 |
| Diámetro interior | 69.85 mm |
| Diámetro exterior | 107.95 mm |
| Espesor | 50.8 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE