


Rodamiento de agujas GBRI487232-IKO - GBRI487232-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri487232-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
76.200 (3)	GBRI 487232	1 970	76.200 (3)	114.300 (4 1/2)	50.800 (2)	51.050	88.900 (3 1/2)

Standard mounting dimensions mm				Ball diam. mm C	Basic load rating N	Limiting load rating N	Allowable rotational speed (P) rpm	Assembled inner ring
d _a Min.	d _a Max.	D _a Max.	r _{as max} (°)					
83.5	86	106.3	1.5	221 000	488 000	1 700	LRBZ 485632	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952377971
Diámetro interior	76.2 mm
Diámetro exterior	114.3 mm
Espesor	50.8 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE