

## Rodamiento de agujas RNA49-14-U-IKO - RNA49-14-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/rna49-14-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
<b>18</b>	---	<b>RNA 49/14U</b>	---	---	19.7	18	26	13	0.3
Standard rounding dimension $D_s$ Max. mm									
	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed (reference speed) rpm						
24	9 260	10 800	11 000						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952378848
Diámetro interior	18 mm
Diámetro exterior	26 mm
Espesor	13 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE