

Rodamiento de agujas RNA6909-U-IKO - RNA6909-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/rna6909-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
52	—	—	—	RNA 6909U	355	52	68	40	0.6
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (1)	Allowable rotational speed (2)					
	N	N	rpm	rpm					
	64	66 600	127 000	3 500					

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952379319
Diámetro interior	52 mm
Diámetro exterior	68 mm
Espesor	40 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE