Rodamiento de agujas
RNA4915-U-IKO - RNA4915-U-IKO

https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/rna4915-u-iko



IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, Without Inner Ring

RNA49···U

Shaft dia. mm	Identification number: With two seals	With one seal	With two seals	With one seal	Mass (Ref.) g	Boundary dimensions mm: F_w	D	C	$r_{s\,min}$ (1)
85	—	RNA 4915U	—	—	520	85	105	30	1

Standard mounting dimension D_a Max. mm	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed (2) rpm
100	79 600	153 000	2 000

Notes(1) Minimum allowable value of chamfer dimension r

(2) Allowable rotational speed applies to grease lubrication.

Remarks1. The outer ring has an oil groove and an oil hole.

2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

123BEARING

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952379647
Diámetro interior	85 mm
Diámetro exterior	105 mm
Espesor	30 mm
Envasado	1

contacto@123rodamiento.es
911 436 830
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE