


Rodamiento de agujas RNA6916-UU-IKO - RNA6916-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/rna6916-uu-iko>

I KO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
90	—	—	RNA6916UU	—	1 010	90	110	54	1
Standard mounting diameter D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)						
105	132 000	317 000	2 000						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	I KO
Nº Ean13	3663952379708
Diámetro interior	90 mm
Diámetro exterior	110 mm
Espesor	54 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE