

Rodamiento de agujas RNA6918-UU-IKO - RNA6918-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/rna6918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref) g | Boundary dimensions mm | | | |
|---|-------------------------------|--------------------------------|--------------------------------|---------------|-----------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 105 | — | — | RNA 6918UU | — | 1 360 | 105 | 125 | 63 | 1.1 |
| Standard mounting dimension D_s Max. mm | | | | | | | | | |
| | Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed (2) | | | | | | |
| | N | N | rpm | | | | | | |
| | 118.5 | 172 000 | 471 000 | 1 800 | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952379791 |
| Diámetro interior | 105 mm |
| Diámetro exterior | 125 mm |
| Espesor | 63 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE