

## Rodamiento de agujas NA6901-U-IKO - NA6901-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na6901-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm					
	With two seals	With one seal	With two seals		With one seal	d	D	C	B	
12	—	—	—	—	<b>NA 6901U</b>	45.5	12	24	22	23

r <sub>s</sub> min ( <sup>1</sup> )	F <sub>w</sub>	Standard mounting dimensions mm			Basic rating C <sub>0</sub>	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	16	14	15	22	15 500	20 400	12 000	LRTZ 121623

Notes: (1) Minimum allowable value of shaft diameter r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952381107
Diámetro interior	12 mm
Diámetro exterior	24 mm
Espesor	23 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE