

Rodamiento de agujas NA6906-U-IKO - NA6906-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na6906-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|----|----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B | |
| 30 | — | — | — | — | NA 6906U | 185 | 30 | 47 | 30 | 31 |

| r _s min (¹) | F _w | Standard mounting dimensions mm | | Basic static load rating C ₀ N | Basic dynamic load rating C ₁₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | |
|--|----------------|------------------------------------|---------------------|---|---|--|----------------------|-------------|
| | | d _s Min. | d _s Max. | | | | | |
| 0.3 | 35 | 32 | 34 | 45 | 40 100 | 63 000 | 5 500 | LRTZ 303531 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952381398 |
| Diámetro interior | 30 mm |
| Diámetro interior | 1.181" inch |
| Diámetro exterior | 47 mm |
| Diámetro exterior | 1.85" inch |
| Espesor | 31 mm |
| Espesor | 1.22" inch |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE