

Rodamiento de agujas NA4911-U-IKO - NA4911-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na4911-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
55	—	NA 4911 U	—	—	415	55	80	25	26

r _s min ⁽¹⁾ F _w	Standard mounting dimensions mm			Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	Max.					
1	63	60	61	75	52 200	85 700	3 000	LRTZ 556326

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952381626
Diámetro interior	55 mm
Diámetro exterior	80 mm
Espesor	26 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE