


Rodamiento de agujas
NA6915-UU-IKO - NA6915-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na6915-uu-iko>

**MACHINED TYPE NEEDLE ROLLER BEARINGS**
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
75	—	—	NA 6915UU		1 480	75	105	54	55

r _s mm	(1)	F _N	Standard mounting dimensions mm		Basic rating C	Basic load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
			d _s Min.	d _s Max.				
1	85	80	83	100	128 000	299 000	2 000	LRTZ 758555

Notes(1)

Minimum allowable value of chamfer dimension r

(2)

Allowable rotational speed applies to grease lubrication.

Remark(1)

The outer ring has an oil groove and an oil hole.

2

Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952381800
Diámetro interior	75 mm
Diámetro exterior	105 mm
Espesor	55 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE