


Rodamiento de agujas NA4916-U-IKO - NA4916-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na4916-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
80	—	NA 4916U	—	—	860	80	110	30	31

r _s min ⁽¹⁾ F _w	Standard mounting dimensions mm			Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	D _s Max.					
1	90	85	88	105	80 700	158 000	2 000	LRTZ 809031

Notes: (1) Minimum allowable value of shaft dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952381824
Diámetro interior	80 mm
Diámetro exterior	110 mm
Espesor	31 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE