

## Rodamiento de agujas NA6917-UU-IKO - NA6917-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na6917-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
85	—	—	NA 6917UU	—	2 360	85	120	63	64

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed(2) rpm	Assembled inner ring LRTZ 8510064
		d <sub>s</sub> Min.	d <sub>s</sub> Max.				
1.1	100	91.5	98	113.5	168 000	448 000	1 900

Notes(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952381886
Diámetro interior	85 mm
Diámetro exterior	120 mm
Espesor	64 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE