

Rodamiento de agujas NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na4918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
90	NA 4918UU	—	—	—	1 360	90	125	35	36

r _s mm	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.					D _s Max.
1.1	105	96.5	103	118.5	106 000	238 000	1 800	LRTZ 9010536

Notes: (1) Minimum allowable value of outer diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952381893
Diámetro interior	90 mm
Diámetro exterior	125 mm
Espesor	36 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE