

Rodamiento de agujas NA4922-UU-IKO - NA4922-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na4922-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
110	NA 4922UU	—	—	—	2 150	110	150	40	41

r _s mm	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		d _s Min.	d _s Max.					
1.1	125	116.5	123	143.5	140 000	322 000	1 500	LRTZ 11012541

Notes: (1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382005
Diámetro interior	110 mm
Diámetro interior	4.331" inch
Diámetro exterior	150 mm
Diámetro exterior	5.906" inch
Espesor	41 mm
Espesor	1.614" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE