

## Rodamiento de agujas NA4928-UU-IKO - NA4928-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/na4928-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
140	NA 4928UU	—	—	—	4 340	140	190	50	51

  

r <sub>s</sub> mm	F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.					
1.5	160	148	158	182	214 000	549 000	1 200	LRTZ 14016051

Notes: (1) Minimum allowable value of shaft diameter r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382050
Diámetro interior	140 mm
Diámetro exterior	190 mm
Espesor	51 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE