


Rodamiento de agujas BR142216-U-IKO - BR142216-U-IKO

https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/br142216-u-iko

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
22.225 ($\frac{7}{8}$)		BR 142216 U	76	22.225 ($\frac{7}{8}$)	34.925 (1 $\frac{7}{8}$)	25.400 (1)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ⁽²⁾		
D_1 Max.	r_{as} max ⁽¹⁾	N	N	rpm		
29.7	1.0	21 600	26 900	9 000		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382135
Diámetro interior	22.225 mm
Diámetro exterior	34.925 mm
Espesor	25.4 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE