


## Rodamiento de agujas BR405228-U-IKO - BR405228-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/br405228-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>63.500</b> (2 1/2)		<b>BR 405228 U</b>	499	63.500 (2 1/2)	82.550 (3 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Basic dynamic load rating $C$	Static load rating $C_0$	Allowable rotational speed <sup>(2)</sup>		
$D_1$ Max.	$r_{as}$ max (1)	N	N	rpm		
74.3	2.0	94 600	174 000	3 000		

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952382340
Diámetro interior	63.5 mm
Diámetro exterior	82.55 mm
Espesor	44.45 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE