

Rodamiento de agujas BR526828-U-IKO - BR526828-U-IKO

https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/br526828-u-iko

BR526828-U

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|------------------------------------|---------------------------|---------------------|---|-----------------|----------------|
| | With two seals | With one seal | | F _w | D | C |
| | BR 526828 U | | | | | |
| 82.550 (3 1/4) | | | 991 | 82.550 (3 1/4) | 107.950 (4 1/4) | 44.450 (1 3/4) |
| Standard mounting dimensions mm | | Basic dynamic load rating | Static load rating | Allowable rotational speed ^(*) | | |
| D_4 | $F_{a \text{ max}}$ ^(†) | C | C ₀ | rpm | | |
| | Max. | N | N | | | |
| | | 109 000 | 227 000 | 2 500 | | |

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952382418 |
| Diámetro interior | 82.55 mm |
| Diámetro exterior | 107.95 mm |
| Espesor | 44.45 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE