


## Rodamiento de agujas BR607632-U-IKO - BR607632-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/br607632-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>95.250</b> (3 3/4)		<b>BR 607632 U</b>	1 161	95.250 (3 3/4)	120.650 (4 3/4)	50.800 (2 )
Standard mounting dimensions mm		Basic dynamic load rating	Static load rating	Allowable rotational speed <sup>(2)</sup>		
$D_s$	$r_{as}$ max	$C$	$C_0$	rpm		
111.4	2.5	148 000	287 000	2 000		

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382456
Diámetro interior	95.25 mm
Diámetro exterior	120.65 mm
Espesor	50.8 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE