


## Rodamiento de agujas BRI82016-UU-IKO - BRI82016-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bri82016-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>12.700</b> (.50)	<b>BRI 82016 UU</b>		<b>99</b>	<b>12.700</b> (.50)	<b>31.750</b> (1.25)	<b>25.400</b> (1.0)	<b>25.650</b>	

$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring <b>LRBZ 81216 B</b>
	Min.	Max.				
<b>19.050</b> (.75)	<b>17.5</b>	<b>18</b>	<b>20 700</b>	<b>24 400</b>	<b>10 000</b>	

Notes: (\*) Minimum allowable value of diameter dimension r.  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382494
Diámetro interior	12.7 mm
Diámetro exterior	31.75 mm
Espesor	25.4 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE