

Rodamiento de agujas BRI102216-U-IKO - BRI102216-U-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bri102216-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
15.875 ($\frac{5}{8}$)		BRI 102216 U	113.5	15.875 ($\frac{5}{8}$)	34.925 (1 $\frac{3}{4}$)	25.400 (1)	25.650	
F_w	Standard mounting dimensions (mm)			Ball dynamic load rating C N	Ball static load rating C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 101416 B	
	Min.	Max.	Max.					
22.225 ($\frac{7}{8}$)	21	21.2	29.7	0.6	21 600	26 900	9 000	

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382517
Diámetro interior	15.875 mm
Diámetro exterior	34.925 mm
Espesor	25.4 mm
Peso	150 g
Envasado	-
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE