


## Rodamiento de agujas BRI122416-UU-IKO - BRI122416-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bri122416-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>19.050</b> (3/4)	<b>BRI 122416 UU</b>		<b>127</b>	19.050 (3/4)	38.100 (1 1/2)	25.400 (1)	25.650	
F <sub>w</sub>	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring		
	Min.	Max.				Min.	Max.	
25.400 (1)	24	24.4	32.9	0.6	23 600	31 300	8 000	<b>LRBZ 121616 B</b>

Notes: (1) Minimum allowable value of diameter dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382531
Diámetro interior	19.05 mm
Diámetro exterior	38.1 mm
Espesor	25.4 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE