


## Rodamiento de agujas BRI264120-UU-IKO - BRI264120-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bri264120-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>41.275</b> (1 13/16)	<b>BRI 264120 UU</b>		<b>386</b>	<b>41.275</b> (1 13/16)	<b>65.088</b> (2 3/8)	<b>31.750</b> (1 1/4)	<b>32.000</b>

F <sub>w</sub>	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 263220 B
	Min.	Max.	Max. as max. (*)				
<b>50.800</b> (2 )	<b>48</b>	<b>49</b>	<b>57.8</b>	<b>51 000</b>	<b>89 400</b>	<b>4 000</b>	

Notes: (\*) Minimum allowable value of chamfer dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382692
Diámetro interior	41.275 mm
Diámetro exterior	65.088 mm
Espesor	31.75 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE