

## Rodamiento de agujas BRI325228-UU-IKO - BRI325228-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bri325228-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>50.800</b> (2)	<b>BRI 325228 UU</b>		<b>889</b>	50.800 (2)	82.550 (3 $\frac{1}{2}$ )	44.450 (1 $\frac{3}{4}$ )	44.700
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring <b>LRBZ 324028 B</b>
	Min.	Max.	Max. as max. <sup>(1)</sup>				
63.500 (2 $\frac{1}{2}$ )	58	61	74.3	1.5	94 600	174 000	3 000

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382739
Diámetro interior	50.8 mm
Diámetro exterior	82.55 mm
Espesor	44.45 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE