


## Rodamiento de agujas BRI527632-UU-IKO - BRI527632-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bri527632-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>82.550</b> (3 1/4)	<b>BRI 527632 UU</b>		<b>1 851</b>	<b>82.550 (3 1/4)</b>	<b>120.650 (4 3/4)</b>	<b>50.800 (2 )</b>	<b>51.050</b>
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
<b>95.250 (3 3/4)</b>	<b>91</b>	<b>93</b>	<b>148 000</b>	<b>287 000</b>	<b>2 000</b>	<b>LRBZ 526032 B</b>	

Notes: (\*) Minimum allowable value of shaft diameter  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952382821
Diámetro interior	82.55 mm
Diámetro exterior	120.65 mm
Espesor	50.8 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE