


## Rodamiento de agujas GBR283720-UU-IKO - GBR283720-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr283720-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>44.450</b> (1.75)	<b>GBR 283720 UU</b>		230	44.450 <sup>(1)</sup> <sub>(1.75)</sub>	58.738 <sup>(2)</sup> <sub>(2.3125)</sub>	31.750 <sup>(1)</sup> <sub>(1.25)</sub>
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_s$ Max.	$r$ as max (°)	N	N	rpm		
53.7	0.6	58 900	114 000	1 800		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(°) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952383033
Diámetro interior	44.45 mm
Diámetro exterior	58.738 mm
Espesor	31.75 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE