


## Rodamiento de agujas GBR526828-UU-IKO - GBR526828-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbr526828-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>82.550</b> (3 1/4)	<b>GBR 526828 UU</b>		960	82.550 (3 1/4)	107.950 (4 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$ Max.	$r$ as max ( <sup>(†)</sup> )	N	N	rpm		
99.9	1.5	127 000	231 000	950		

Notes: (\*) Minimum allowable value of diameter dimension  $r$   
(†) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952383170
Diámetro interior	82.55 mm
Diámetro exterior	107.95 mm
Espesor	44.45 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE