


Rodamiento de agujas GBRI243920-UU-IKO - GBRI243920-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri243920-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
38.100 (1 1/2)	GBRI 243920 UU		400	38.100 (1 1/2)	61.912 (2 3/8)	31.750 (1 1/4)

B	F_w	Standard mounting dimensions - mm			$r_{as\ max}$ (1)	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	D_s Max.					
32.000	47.625 (1 7/8)	43.3	45	56.2	1	61 100	121 000	1 700	LRBZ 243020

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952383477
Diámetro interior	38.1 mm
Diámetro exterior	61.912 mm
Espesor	31.75 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE