

## Rodamiento de agujas GBRI406028-UU-IKO - GBRI406028-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/gbri406028-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
<b>63.500</b> (2 1/2)	<b>GBRI 406028 UU</b>		1 140	63.500 (2 1/2)	95.250 (3 7/8)	44.450 (1 3/4)

  

B	F <sub>w</sub>	Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>min</sub>	d <sub>max</sub>	D <sub>s</sub> Max.					r <sub>as max</sub> <sup>(1)</sup>
44.700	76.200 (3)	71	73	88	1.5	101 000	215 000	1 100	<b>LRBZ 404828</b>

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952383569
Diámetro interior	63.5 mm
Diámetro exterior	95.25 mm
Espesor	44.45 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE