

## Rodamiento de agujas NAFW203732-IKO - NAW203732-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/naw203732-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring

Shaft dia. mm	Identification number	Mess (Ref.)	Boundary dimensions mm					Standard mounting dimensions mm				
		g	d	D	C	r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	d <sub>b</sub>	D <sub>2</sub> Max.	d <sub>4</sub> Min.	D <sub>4</sub> Max.	D <sub>b</sub>
20	<b>NAFW 203732</b>	158	20	37	32	0.3	25	30.4	35	22	24	25.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>	Assembled roller ring									
N	N	rpm	LRT 202532									
33 200	49 000	20 000										

Notes: (1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952384535
Diámetro interior	20 mm
Diámetro exterior	37 mm
Espesor	32 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE