


## Rodamiento de agujas NAFW355034-IKO - NAW355034-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nafw355034-iko>

**IKO**  
**NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE**  
With Inner Ring



Shaft dia. mm	Identification number	Mess (Ref.)	Boundary dimensions mm					Standard mounting dimensions mm				
		g	d	D	C	r <sub>s</sub> min <sup>(1)</sup>	F <sub>w</sub>	d <sub>b</sub> Max.	D <sub>3</sub> Min.	d <sub>4</sub> Max.	D <sub>b</sub> Max.	
35	NAFW 355034	230	35	50	34	0.3	40	43.5	48	37	39	40.8
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>	Assembled roller ring									
N	N	rpm	LRT 354034									
38 000	85 400	12 000										

Notes:  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952384641
Diámetro interior	35 mm
Diámetro exterior	55 mm
Espesor	34 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE