


Rodamiento de agujas NAU4906-IKO - NAU4906-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nau4906-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings
Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ r _{s min}	J	E _w
30	—	NAU 4906	102	30	47	17	0.3	34	41.5
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾							
N	N	rpm							
13 000	16 200	12 000							

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952385280
Diámetro interior	30 mm
Diámetro exterior	47 mm
Espesor	17 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE