


## Rodamiento de agujas TRU426230-UU-IKO - TRU426230-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/tru426230-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings **[With Seal]**  
Full Complement Roller Bearings **[With Seal]**



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> min	J
42	—	TRU 426230UU	290	42	62	30	0.6	48
<i>E<sub>w</sub></i>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>2</sub> rpm					
56.5	34 600	57 800	4,000					

Notes: (1) Minimum allowable value of chamfer dimension r.  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952386140
Diámetro interior	42 mm
Diámetro exterior	62 mm
Espesor	30 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE